

AD-A244 169

MENTATION PAGE

Form Approved  
OMB No. 0704-0188

1a. F



2a. SECURITY CLASSIFICATION AUTHORITY

2b. DECLASSIFICATION/DOWNGRADING SCHEDULE

4. PERFORMING ORGANIZATION REPORT NUMBER(S)

6a. NAME OF PERFORMING ORGANIZATION

Massachusetts Inst. of Tech.

6c. ADDRESS (City, State, and ZIP Code)

Haystack Observatory  
Cambridge, MA 02139

8a. NAME OF FUNDING/SPONSORING ORGANIZATION

AFOSR

8c. ADDRESS (City, State, and ZIP Code)

Building 410  
Building AFB DC 20332-6448

6b. OFFICE SYMBOL  
(If applicable)

AFOSR/NC

8b. OFFICE SYMBOL  
(If applicable)

NC

1b. RESTRICTIVE MARKINGS

3. DISTRIBUTION/AVAILABILITY OF REPORT

Approved for public release; Distribution is unlimited

5. MONITORING ORGANIZATION REPORT NUMBER(S)

7a. NAME OF MONITORING ORGANIZATION

AFOSR/NC

7b. ADDRESS (City, State, and ZIP Code)

Building 410, Bolling AFB, D.C.  
20332-6448

9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER

AFOSR 89 0169

10. SOURCE OF FUNDING NUMBERS

PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
6104D	3842	A2	

11. TITLE (Include Security Classification)

(DURIP) Instrumentation Support for High-Latitude Ionospheric Research and the Establishment of a Dual Radar/Dual Frequency Observational Capability at the Millstone Radar Facility.

12. PERSONAL AUTHOR(S)

John C. Foster

13a. TYPE OF REPORT

Final

13b. TIME COVERED

FROM 12/88 TO 6/91

14. DATE OF REPORT (Year, Month, Day)

'91/10/28

15. PAGE COUNT

6

16. SUPPLEMENTARY NOTATION

17. COSATI CODES

FIELD	GROUP	SUB-GROUP

18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)

DURIP, radar, ionosphere

19. ABSTRACT (Continue on reverse if necessary and identify by block number)

Radar receiver and signal processing instrumentation was acquired and fabricated in order to establish a capability for dual 440 MHz and 1390 MHz radar operations at the M.I.T. Millstone Hill research facility. Hardware costs for a duplicate of the MIDAS radar processor were provided. This instrumentation enables a program of simultaneous, high-spatial resolution dual frequency observations of non-thermal and coherent radar backscatter from ionospheric plasma waves and turbulence at both F and E region heights. Simultaneous operation of the fully steerable Millstone Hill UHF and L-band radars in the incoherent scatter mode addresses the spatial homogeneity and simultaneity of ionospheric effects and processes.

91-19218



20. DISTRIBUTION/AVAILABILITY OF ABSTRACT

☐ UNCLASSIFIED/UNLIMITED ☐ SAME AS RPT ☐ DTIC USERS

21. ABSTRACT S

Unclassified

22a. NAME OF RESPONSIBLE INDIVIDUAL

J. G. Stobie, Lt. Col., USAF

22b. TELEPHONE (Include Area Code)

(202) 767-4960

22c. OFFICE SYMBOL

AFOSR/NC

## COMPLETED PROJECT SUMMARY

1. TITLE: (DURIP) Instrumentation Support for High-Latitude Ionospheric Research and the Establishment of a Dual Radar/Dual Frequency Observational Capability at the Millstone Radar Facility

2. PRINCIPAL INVESTIGATOR: Dr. J. C. Foster  
M.I.T. Haystack Observatory  
Westford, MA 01886

3. INCLUSIVE DATES: 1 December 1988 - 30 June 1991

4. GRANT NUMBER: AFOSR-89-0169

5. COSTS AND FY SOURCE: \$62,235 FY 89


6. SENIOR RESEARCH PERSONNEL:  
Dr. J. C. Foster

7. JUNIOR RESEARCH PERSONNEL:  
Mr. A. D. Pailes

8. PUBLICATIONS: not applicable

### 9. ABSTRACT OF OBJECTIVES AND ACCOMPLISHMENTS:

Radar receiver and signal processing instrumentation was acquired and fabricated in order to establish a capability for dual 440 MHz and 1390 MHz radar operations at the M.I.T. Millstone Hill research facility. Hardware costs for a duplicate of the MIDAS radar processor were provided. This instrumentation enables a program of simultaneous, high-spatial resolution dual frequency observations of non-thermal and coherent radar backscatter from ionospheric plasma waves and turbulence at both *F* and *E* region heights. Simultaneous operation of the fully steerable Millstone Hill UHF and L-band radars in the incoherent scatter mode addresses the spatial homogeneity and simultaneity of ionospheric effects and processes.



Acquisition To:	
NTIS (CRS)	J
DTIC (NS)	
Unprocessed	
J. C. Foster	
By:	
Signature:	
Date:	
A-1	

**FINAL SCIENTIFIC REPORT**

submitted to the  
Air Force Office of Scientific Research

by  
Massachusetts Institute of Technology

for  
AFOSR-88-0169

**(DURIP) INSTRUMENTATION SUPPORT FOR  
HIGH-LATITUDE IONOSPHERIC RESEARCH AND THE ESTABLISHMENT  
OF A  
DUAL RADAR/DUAL FREQUENCY OBSERVATIONAL CAPABILITY  
AT THE MILLSTONE RADAR FACILITY**

in

Fiscal Years 1989 - 1991

## Introduction

The MIDAS (Millstone Ionospheric Data Acquisition System) signal processing, radar control, and receiver system was developed under National Science Foundation support for use with the 440 MHz UHF Atmospheric Sciences radar at Millstone Hill. MIDAS has been designed as a highly modular system based on industry standards using "off-the-shelf" components wherever possible. The standards adopted were Ethernet and RS232 for communications between loosely coupled system modules, VME bus for communications between tightly coupled modules, Unix-based operating systems for the real-time system software and the C programming language. Hardware for a prototype MIDAS system and engineering and personnel costs associated with MIDAS design, fabrication, and testing have been provided by NSF. A block diagram of the MIDAS system hardware is presented in Figure 1.

Under this DURIP instrumentation grant, radar receiver and signal processing hardware, following the prototype design, has been acquired for a second MIDAS system for use with the M.I.T. Lincoln Laboratory L-band radar in order to establish a capability for dual 440 MHz and 1390 MHz radar operations at the M.I.T. Millstone Hill research facility. This instrumentation enables a program of simultaneous, high-spatial resolution dual frequency observations of non-thermal and coherent radar backscatter from ionospheric plasma waves and turbulence at both  $F$  and  $E$  region heights. Simultaneous operation of the fully steerable Millstone Hill UHF and L-band radars in the incoherent scatter mode addresses the spatial homogeneity and simultaneity of ionospheric effects and processes.

### Instrumentation Acquired:

Under this DURIP award, funding was provided for the major system modules and electrical components of a second MIDAS receiver and processing system. All components were purchased, and fabrication and system integration has proceeded in parallel with the NSF-supported prototype system. Personnel costs associated with the fabrication, testing, and integration of the DURIP MIDAS system have been borne by the NSF and the schedule for this work has been set in accordance with the NSF program. The current schedule is for the DURIP MIDAS system to be fully operational and integrated into the Atmospheric Sciences system by mid-1992.

MIDAS system modules and components acquired under DURIP support are as follows.

Item	Cost
Radar Processor	
Mercury 3232 Array Processor	18,360
SUN 3E120 Computer cards	7,300
Ironics IV1624A Controller	2,640
VME Crate	6,400
Total Pre-fabricated Radar Processor Modules	34,700
Receiver	
PTS 500 Frequency Synthesizer	8,000
PTS 40 Frequency Synthesizer	8,000
Datacom and RF Boards	6,300
Total Pre-fabricated Receiver Modules	22,300
Electronics Components & Supplies	<u>5,235</u>
TOTAL DURIP Equipment	62,235

#### Research Projects using DURIP Instrumentation

a) As Proposed: The frequency dependence of coherent radar backscatter from *F* region ionospheric irregularities generated by current driven instabilities will be investigated in experiments using simultaneous observations with the Millstone Hill UHF and L-band radars. Recent UHF and VHF observations of this phenomena at auroral latitudes with the EISCAT radars further suggest that such frequency-dependent characteristics play an important role in understanding enhanced radar backscatter. Several specific projects using the DURIP instrumentation at Millstone Hill have already been proposed. A dual-radar/rocket research program has been proposed to NASA for 1995 to investigate this topic using a rocket-borne electron beam device to drive local currents and generate the phenomena of interest. Continued research on the occurrence and characteristics of the *F* region radar returns, making use of the DURIP equipment to help differentiate current driven instabilities from false returns, has been proposed to AFOSR for a three year period beginning in 1992. In addition, Dr. Keith M. Groves, a recent graduate of MIT whose area of specialization included this topic, plans to continue a research program in this area using the enhanced Millstone Hill facilities.

b) New Research Areas: *E* region plasma waves and turbulence are produced in the presence of intense ionospheric currents and heating. Initial studies using the narrow beam and great sensitivity of the Millstone Hill UHF radar will be extended to a program of dual frequency observations under a project proposed to AFOSR. The co-location of two large, fully steerable radars, as enabled by the DURIP instrumentation, has created a unique capability to investigate the processes which lead to intense clutter returns for VHF and UHF radars operating in the high-latitude environment. An additional capability of the DURIP equipment is to observe the coherent *E* region returns with one radar system while doing simultaneous incoherent scatter diagnostics of background plasma conditions using the other radar.

A second new research area utilizing the DURIP instrumentation is that of dual antenna UHF incoherent observations of ionospheric phenomena using the 68 m fixed and 46 m steerable antennas at Millstone Hill. Here the DURIP instrumentation creates the capability of receiving and integrating signals from both antennas simultaneously. Locally propagating phenomena, such as gravity waves, can best be diagnosed with such a technique. Dual antenna operations will also provide the capability of examining the spatial homogeneity and simultaneity of ionospheric phenomena.

#### Professional Personnel

Dr. J. C. Foster - Principal Investigator

Mr. A. D. Pailes - Electrical Engineering

